

# PRODUCT SPECIFICATION SHEET

## LP2 LED Paver




Rev. C3



Large LED paver fitting. Available in either stainless steel or hard anodised aluminum.

The LP2, which is identical in size and shape to its counterpart the LP1, can be supplied in 316 stainless steel or hard anodised aluminum.

The internal lens has been replaced with a frosted glass cover to provide a soft wash of light across the area or object being illuminated. The fitting comes with a warm white or neutral white LED light and optional dimming functionality, for added control over your lighting.



Please note that all dimensions are shown in mm



### TECHNICAL INFORMATION

Illuminator	LED
Operating Environment	Outdoor
Material	Stainless steel or hard anodised aluminum
Finishes	Black, silver, custom RAL to order
Mounting Hole Size	42mm (1.65")
Power Consumption	1.12w per fitting
Voltage	3.2v nominal
Color Temp. & CRI	3000K - 96CRI (typical) / 4000K - 95CRI (typical)
Typical Luminous Flux (based on 15° lens)	3000K: 38lm/W / 4000K: 39lm/W
Glass	Frosted glass front
Beam Angle	75°

### DRIVER CONTROL OPTIONS (Depending on specified driver)

No Dimming	Local Potentiometer Dimming
0-10V Dimming	Remote Potentiometer Dimming

### PRODUCT CODES

MODEL	OPTICS	COLOR TEMP	MATERIAL	FINISH
UFO LP2	None NL	3000K 30	Stainless Steel SS	Black BL
		4000K 40	Hard Anodised HA	Silver SV
				No color NC
				Custom CU

UFO LP2				
e.g. UFO LP2-NL-30-SS-BL				



Universal Fibre Optics Ltd  
Home Place \ Coldstream  
TD12 4DT \ UK  
+44 (0)1890 883416 \ [www.ufo.lighting](http://www.ufo.lighting)

Universal Fiber Optic Lighting USA, LLC  
1749 Northgate Blvd  
Sarasota \ FL34234 \ USA  
941-343-8115 \ [www.fiberopticlighting.com](http://www.fiberopticlighting.com)

UFO Licht GmbH  
Andreasstraße 20  
93059 Regensburg \ Deutschland  
+49 (0)9491 955880 \ [www.ufo-licht.de](http://www.ufo-licht.de)