

PRODUCT SPECIFICATION SHEET



Rev. C3


LP1 LED Paver



Large LED paver fitting. Available in either stainless steel or hard anodised aluminum.

This fitting can be specified with a warm white or neutral white LED light and a narrow or wide optic allowing for a choice of light spread. Multiple dimming options are also supported with a UFO approved dimmer switch giving you greater control over your lighting.

Internally, the LP1 contains a lens that allows you to focus the light where it is needed most and a recessed dark cone that reduces glare for applications where walkover is expected.



Note that all dimensions are shown in mm



TECHNICAL INFORMATION

Illuminator	LED
Operating Environment	Outdoor
Material	Stainless steel or hard anodised aluminum
Finishes	Hard anodised - black, silver, custom RAL Stainless steel - natural
Mounting Hole Size	42mm
Power Consumption	1W per fitting
Voltage	3.2V nominal
Color Temp. & CRI	3000K - 96CRI (typical) / 4000K - 95CRI (typical)
Typical Luminous Flux (based on 15° lens)	3000K: 76lm/W / 4000K: 87lm/W
Optics	15° / 51°

DRIVER CONTROL OPTIONS (Depending on specified driver)

No Dimming	Local Potentiometer Dimming
0-10V Dimming	Remote Potentiometer Dimming

PRODUCT CODES

MODEL	OPTICS	COLOR TEMP	MATERIAL	FINISH
UFO LP1	15° 15	3000K 30	Stainless Steel SS	Black BL
	51° 51	4000K 40	Alu, Hard Anodised HA	Silver SV
				No colour NC
				Custom CU



e.g, UFO LP1-15-30-SS-BL

