

PRODUCT SPECIFICATION SHEET



Rev. C1

UFO P21 Paver



Our range of classic paver fittings are all manufactured from hard wearing, corrosion resistant 316 stainless steel, and fitted with high quality toughened glass.

Available in a wide range of sizes, paver fittings can generally be used with fiber sizes ranging from 2mm up to 8mm diameter. This is dependant on the size of ferrule the fitting can accept.

All pavers are supplied in natural stainless steel and most types are available with a choice of clear or frosted glass.

The P21 is a small walkover paver with a 25mm (0.98") round, bevelled flange and a total depth of 26mm (1.02"). Fitted with a 13mm (0.51") diameter toughened glass front. The P21 uses an 8mm smooth ferrule which is secured with a M4 grub screw. Available with an optional mounting spring to aid installation.

TECHNICAL INFORMATION	
Lens	30mm (1.18"), clear or frosted
Beam angle	54°
Material	316 Stainless steel
Finishes available	Stainless steel
Weight	29.3g (0.06lb)
Mounting hole size	19mm (0.75")
Ferrule size	M10 or 8mm
Min. fiber size	2mm
Max. fiber size	6mm

ORDERING CODES				
MODEL	LENS		FERRULE SIZE	
UFO P21	Clear	C	M10	M10
	Frosted	F	8mm	8mm
UFO P21				

